


Arda

kvadrat


Arda



961



991




771



161



791



931



321



131



211



201



671



351



Arda

Abrasion

Approx. 50.000 Martindale rubs, EN ISO 12947

Abrasion test results exceeding ACT performance guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention.

Pilling

Note 4-5, EN ISO 12945

Lightfastness

Note 5-7 ISO 105-B02

Fastness to rubbing

Dry note 3-5 ISO 105-X12

Wet note 3-5 ISO 105-X12

Absorption

0.40/Class D (flat), EN ISO 354

Airflow

156 Pa s/m EN 29053

Flame resistance

ASTM E84 Class A Unadhered

AS/NZS 3837 class 2

BS 5852 part 1

BS 5852 crib 5 with treatment *

DIN 4102 B2

EN 1021-1/2

IMO FTP Code 2010 Part 8

UNI 9175 1IM

US Cal. Bull. 117-2013

Free from added flame-retardant chemicals as standard

** To pass this test flame retardant treatment is necessary. We are looking into more environmental friendly alternatives but for now, the external finisher may use a treatment containing halogen-based flame retardants*

Arda

Design: Front

Type: Upholstery

Composition: 70% new wool, 21% polyester, 9% nylon

Yarn type: Worsted

Binding: Knit

Width: Approx. 142 cm, 56 inches

Weight: Approx. 800 g/lin.m, 28 oz/ly

Repeat: None

Colour difference may occur

Cleaning: Vacuum clean frequently, ideally every week if fixed covers. Remove stains as soon as they occur, with clean warm water or sparkling water. Extraction clean when necessary. Extraction cleaning might dissolve water-based glue. Pay attention to temperature and amount of cleaning fluid.

Also washable at 30°C, half wash load. Drip drying. Mount in moist condition. Shrinkage max. 5% at 30°C.

Disinfection, see kvadrat.dk

More info: Care and maintenance kvadrat.dk



5 year
warranty



Acoustic



kvadrat

ACT Guidelines Knit fabrics

Flammability

US Cal. Bull. 117-2013

Dry & Wet Crocking AATCC 8

Dry Crocking: Grade 4.5

Wet Crocking: Grade 4.5

Colour Fastness to Light AATCC 16

Grade 5.0 minimum 40 hours

Physical properties

Pilling Class 4-5 ASTM D4970

Breaking Strength warp 85 / weft 288 lbs, ASTM D5034

Seam Slippage warp 88 / weft 137.5 lbs, ASTM D4034

Abrasion ASTM D4966

50.000 cycles Martindale – High Traffic / Public Spaces

Benefits of wool

Wool is a renewable resource

Wool is very comfortable because of its ability to absorb/
give off humidity

Wool is flame retardant

Wool is biodegradable

Wool is naturally soil resistant

Wool ages with grace

Quality benefits

Complies with Möbelfakta

Very good abrasion

Good lightfastness

Flame retardant

Washable

Environmental benefits

Follow the EU Ecolabel dye restrictions incl. AZO dye
and heavy metal restrictions

No use of halogen-based flame retardants (incl. brominated
and chlorinated)

REACH compliant

Californian Proposition 65 list compliant

LBC Red list compliant

No content of PFCs or 'PFAS'

Green building certificates

Greenguard Gold: Low chemical emission

Health Product Declaration (HPD): Declaring textile content
and substance

Country of origin

The Netherlands

Launch

2022

Warranty

5 years. See terms and conditions on kvadrat.dk

Kvadrat packaging and cardboard is recyclable. Cardboard
material is FSC certified and / or contains recycled content.

For further information

kvadrat.dk