







373




133




113




393




183




163



143



673



973



923




993



953


# Naveli




213




243




443




553



453




723



613



643



783



753



563



573



# Naveli

## Abrasion

Approx. 50.000 Martindale rubs, EN ISO 12947

*Abrasion test results exceeding ACT performance guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention*

## Pilling

Note 4-5, EN ISO 12945

## Seam slippage

Seam parallel to warp: 4.6 mm parallel to weft: 4.3 m  
EN ISO 13 936-2 180 Newton

## Lightfastness

Note 6-7 ISO 105-B02

## Fastness to rubbing

Dry note 4-5 ISO 105-X12  
Wet note 4-5 ISO 105-X12

## Flame resistance

AS/NZS 3837 class 2  
ASTM E84 Class A Adhered  
ASTM E84 Class A Unadhered  
BS 5852 Crib 5 with treatment \*  
BS 5852 Part 1  
BS 7176 Low Hazard  
EN 1021-1/2  
IMO FTP Code 2010 Part 8  
NF D 60 013  
SN 198 898 5.3 with treatment \*  
UNI 9175 1IM  
US Cal. Bull. 117-2013  
ÖNORM B1/Q1

Free from added flame-retardant chemicals as standard

*\* To pass this test flame retardant treatment is necessary. We are looking into more environmentally friendly alternatives but for now the external finisher may use a treatment containing halogen-based flame retardants.*

## Naveli

Design: Doshi Levien

Type: Upholstery, panel fabric

Composition: 100% new wool

Yarn type: Worsted

Binding: Plain

Width: Approx. 140 cm, 55 inches

Weight: Approx. 540 g/lin.m, 17 oz/ly

Repeat: None

Colour difference may occur

Foreign fibres may occur in light colours

Cleaning: Vacuum clean frequently, ideally every week. Remove stains as soon as they occur, with clean warm water or sparkling water. Extraction clean when necessary. Pay attention to temperature and amount of cleaning fluid.

Extraction cleaning might dissolve water-based glue. Pay attention to temperature and amount of cleaning fluid.

Disinfection, see kvadrat.dk

More info: Care and maintenance kvadrat.dk



10 year warranty



# kvadrat

## **ACT Guidelines Woven fabrics**

### **Flammability**

US Cal. Bull. 117-2013

### **Dry & Wet Crocking AATCC 8**

Dry Crocking: Grade 4.5-5.0

Wet Crocking: Grade 4.0-5.0

### **Colour Fastness to Light AATCC 16**

Grade 4.0-5.0 minimum 40 hours

### **Physical properties**

Pilling Class 4-5 Martindale ASTM D4970

Breaking Strength warp 149 / weft 147 lbs, ASTM D5034

Seam Slippage warp 55.5 / weft 54.5 lbs, ASTM D4034

### **Abrasion ASTM D4966**

50.000 cycles Martindale – High Traffic / Public Spaces

### **Benefits of wool**

Wool is a renewable resource

Wool is very comfortable because of its ability to absorb/  
give off humidity

Wool is flame retardant

Wool is biodegradable

Wool is naturally soil resistant

Wool ages with grace

### **Quality benefits**

Complies with Möbelfakta

Very good abrasion

Flame retardant

### **Environmental benefits**

Complies with EU Ecolabel

Free of intentionally added PFAS

Mono-material designed for circularity

REACH compliant

Californian Proposition 65 list compliant

LBC Red list compliant

Healthier Hospitals compliant

### **Green building certificates**

Greenguard Gold: Low chemical emission

Environmental Product Declaration (EPD): Based on a LCA  
following EN 15804 and follow the standard of ISO 14040

Health Product Declaration (HPD): Declaring textile content  
and substance

### **Country of origin**

England

### **Launch**

2023

### **Warranty**

10 years. See terms and conditions on kvadrat.dk

Kvadrat packaging and cardboard is recyclable. Cardboard  
material is FSC certified and / or contains recycled content.

For further information

kvadrat.dk