



REFLEX

KVADRAT / RAF SIMONS

REFLEX



339



779




589



129




789



639




119



159




199



449

## KVADRAT/RAF SIMONS



### REFLEX

Design: Raf Simons

Type: Upholstery

Composition: 87% new wool, 8% viscose, 5% nylon

Yarn type: Worsted

Binding: Complex weave

Width: Approx. 143 cm, 56.5 inches

Weight: Approx. 640 g/lin.m, 20.6 oz/ly

Repeat: Approx. V 20 cm, 7.9 inches, H 0 cm, 0 inches

Striped across the width

Foreign fibers may occur in light colours

Cleaning: Vacuum clean frequently, ideally every week.

Remove stains as soon as they occur, with clean warm water or sparkling water. Extraction clean when necessary.

Extraction cleaning might dissolve water-based glue. Pay attention to temperature and amount of cleaning fluid.

Disinfection, see kvadrat.dk

More info: Care and maintenance kvadrat.dk



10 year warranty



### Abrasion

Approx. 100.000 Martindale rubs, EN ISO 12947

*Abrasion test results exceeding ACT performance guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention*

### Pilling

Note 3-4, EN ISO 12945

### Seam slippage

Seam parallel to warp: 4.0 mm parallel to weft: 5.0 mm  
EN ISO 13 936-2 180 Newton

### Lightfastness

Note 5-7 ISO 105-B02

#### Flame resistance

AS/NZS 3837 class 2  
BS 5852 crib 5 with treatment \*  
BS 5852 part 1  
EN 1021-1/2  
IMO FTP Code 2010 Part 8  
NF D 60 013  
ÖNORM B2/Q1  
SN 198 898 5.3 with treatment \*  
UNI 9175 1IM  
US Cal. Bull. 117-2013

Free from added flame retardant chemicals as standard

*\* To pass this test flame retardant treatment is necessary.  
We are looking into more environmentally friendly alternatives but for now, the external finisher may use a treatment containing halogen-based flame retardants*

#### ACT Guidelines Woven fabrics

#### Flammability

US Cal. Bull. 117-2013

#### Dry & Wet Crocking

Dry Crocking: Grade 4.0  
Wet Crocking: Grade 3.0

#### Colour Fastness to Light

Grade 5.0 minimum 40 hours

#### Physical properties

Pilling Class 3-4  
Breaking Strength warp 167 / weft 166 lbs.  
Seam Slippage warp 87 / weft 31 lbs.

#### Abrasion

100.000 cycles Martindale - High Traffic / Public Spaces

#### Benefits of wool

Wool is a renewable resource  
Wool is very comfortable because of its ability to absorb/  
give off humidity  
Wool is flame retardant  
Wool is biodegradable  
Wool is naturally soil resistant  
Wool ages with grace

#### Quality benefits

Complies with Möbelfakta  
Very good abrasion  
Good lightfastness  
Flame retardant

#### Environmental benefits

Follow the EU Ecolabel dye restrictions incl. AZO dye and heavy metal restrictions  
No content of PFCs or 'PFAS'  
REACH compliant  
Californian Proposition 65 list compliant  
LBC Red list compliant  
Healthier Hospitals compliant

#### Green building certificates

Greenguard Gold: Low chemical emission  
Health Product Declaration (HPD): Declaring textile content and substance

#### Country of origin

Norway

#### Warranty

10 years. See terms and conditions on kvadrat.dk

Kvadrat packaging and cardboard is recyclable.

Cardboard material is FSC certified and / or contains recycled content.

For further information

kvadrat.dk