kvadrat

152

163

276

286

133

143

173

113

123

183

842

906

196

954

962

912

923

412

982

933

942

996

973

672

362

Remix 3

346

326

242

356

233

223

126

136

393

682

266

296

406

686

252

692

606

433

783

383

422

452

866

836

733

823

773

796

743

816

753

722

762

716

516

852

873

543

536

632

443

612

373

653

643

566

662

Remix 3
Design: Giulio Ridolfo

Type: Upholstery, panel fabric
Composition: 90% new wool, 10% nylon
Yarn type: Worsted
Binding: Plain
Width: Approx. 140 cm, 55 inches
Weight: Approx. 420 g/lin.m, 13.6 oz/ly

Colour difference may occur

Cleaning: Vacuum clean frequently, ideally every week. Remove stains as soon as they occur, with clean warm water or sparkling water. Extraction clean when necessary. Extraction cleaning might dissolve water-based glue. Pay attention to temperature and amount of cleaning fluid.
Disinfection, see kvadrat.dk

More info: Care and maintenance kvadrat.dk

✶ ✖ ✖ ✐ Ⓟ

10 year warranty

Remix 3

Abrasion
Approx. 100.000 Martindale rubs, EN ISO 12947

Abrasion test results exceeding ACT performance guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention

Pilling
Note 4, EN ISO 12945

Seam slippage
Seam parallel to warp: 5.0 mm parallel to weft: 3.0 mm
EN ISO 13 936-2 180 Newton

Lightfastness
Note 5-7 ISO 105-B02

Fastness to rubbing
Dry note 3-5 ISO 105-X12
Wet note 3-5 ISO 105-X12

Absorption
0.55/Class D (flat), 0.80/Class B (waved) EN ISO 354

Airflow
465 Pa s/m EN 29053

Flame resistance
AS/NZS 1530.3
AS/NZS 3837 class 2
ASTM E84 Class A Unadhered
ASTM E84 Class A Adhered
BS 5852 crib 5 with treatment *
BS 5852 part 1
EN 1021-1/2
EN 13501 B-s2, d0 wrapped, with treatment *
GB 50222 B1 with treatment (Chinese) *
IMO FTP Code 2010 Part 7 with treatment *
IMO FTP Code 2010 Part 8
NF D 60 013
NFPA 260
ÖNORM B1/Q1
SN 198 898 5.3 with treatment *
UNI 9175 1IM
US Cal. Bull. 117-2013

Free from added flame retardant chemicals as standard

* To pass this test flame retardant treatment is necessary. We are looking into more environmentally friendly alternatives but for now, the external finisher may use a treatment containing halogen-based flame retardants

kvadrat

ACT Guidelines Woven fabrics

Flammability
US Cal. Bull. 117-2013

Dry & Wet Crocking
Dry Crocking: Grade 4.5
Wet Crocking: Grade 4.5

Colour Fastness to Light
Grade 4.0 minimum 40 hours

Physical properties
Pilling Class 4
Breaking Strength warp 132 / weft 138 lbs.
Seam Slippage warp 126.5 / weft 130 lbs.

Abrasion
100.000 cycles Martindale – High Traffic / Public Spaces

Benefits of wool
Wool is a renewable resource
Wool is very comfortable because of its ability to absorb/
give off humidity
Wool is flame retardant
Wool is biodegradable
Wool is naturally soil resistant
Wool ages with grace

Quality benefits
Complies with Möbelfakta
Very good abrasion
Good lightfastness
Flame retardant

Environmental benefits
EU Ecolabel compliant
Free of intentionally added PFAS
REACH compliant
Californian Proposition 65 list compliant
LBC Red list compliant
Healthier Hospitals compliant

Green building certificates
Greenguard Gold: Low chemical emission
Environmental Product Declaration (EPD): 3rd Party Verified.
ISO 14025 & EN 15804. Developed in accordance with the
European standard EN 15804+A2.
Health Product Declaration (HPD): Declaring textile content
and substance

Country of origin
United Kingdom

Launch
2007

Warranty
10 years. See terms and conditions on kvadrat.dk

Kvadrat packaging and cardboard is recyclable. Cardboard
material is FSC certified and / or contains recycled content.

For further information
kvadrat.dk

kvadrat