





# Rumor



931




221




141



681




561



751



671



761



741



## Rumor

Design: Bertjan Pot

Type: Upholstery

Composition: 21% new wool, 12% recycled polyester, 7% nylon, 60% recycled polyester filling

Yarn type: Worsted

Binding: Knit

Width: approx. 165 cm, 65 inches

Weight: approx. 1280 g/lin.m, 41 oz/ly

Repeat: None

Colour difference may occur

Foreign fibers may occur in light colours

Cleaning: Vacuuming gently.

Washable at 30°C if loose covers.

Drip drying.

Shrinkage approx. 3%

Mount in moist condition

More info: Care and maintenance [kvadrat.dk](http://kvadrat.dk)



5 year  
warranty



## Rumor

### Abrasion

Approx. 100.000 Martindale rubs, EN ISO 12947

*Abrasion test results exceeding ACT performance guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention*

### Pilling

Note 4-5, EN ISO 12945

### Lightfastness

Note 6-7, ISO 105-B02

### Fastness to rubbing

Dry note 4-5, ISO 105-X12

Wet note 4, ISO 105-X12

### Absorption

150 mm airgap

0.70/Class C (flat), EN ISO 354

100 mm airgap

0.60/Class C (flat), EN ISO 354

### Airflow

360 Pa s/m EN 29035

### Flame resistance

AS/NZS 3837 class 1

ASTM E84 Class A Unadhered

BS 5852 part 1 ignition source 0

BS 5852 Crib 5, with treatment \*

EN 1021-1/2

IMO FTP Code 2010 part 8

UNI 9175 1IM

US Cal. Bull. 117-2013

Free from added flame-retardant chemicals as standard

*\* To pass this test flame retardant treatment is necessary. We are looking into more environmentally friendly alternatives but for now, the external finisher may use a treatment containing halogen-based flame retardants*

## **ACT Guidelines Knit fabrics**

### **Flammability**

US Cal. Bull. 117-2013

### **Dry & Wet Crocking AATCC 8**

Dry Crocking: Grade 5.0

Wet Crocking: Grade 4.0

### **Colour Fastness to Light AATCC 16**

Grade 4.5 minimum 40 hours

### **Physical properties**

Pilling Class 4-5 ASTM D4970

Breaking Strength warp 127 / weft 219 lbs, ASTM D5034

Seam Slippage warp 144 / weft 156 lbs, ASTM D4034

### **Abrasion**

100.000 cycles Martindale – High Traffic / Public Space

### **Quality benefits**

Great wear- and stretchability

Very good abrasion

Good lightfastness

Flame retardant

### **Environmental benefits**

Follow the EU Ecolabel dye restrictions incl. AZO dye and heavy metal restrictions

REACH compliant

No content of PFCs or 'PFAS'

Californian Proposition 65 list compliant

LBC Red list compliant

Healthier Hospitals compliant

### **Green building certificates**

Greengard Gold: Low chemical emission

Health Product Declaration (HPD): Declaring textile content and substance

## **Country of origin**

The Netherlands

## **Launch**

2024

## **Warranty**

5 years. See terms and conditions on kvadrat.dk

Kvadrat packaging and cardboard is recyclable. Cardboard material is FSC certified and / or contains recycled content.

For further information

[kvadrat.dk](http://kvadrat.dk)